

Introducing the UL® Recognized

SETHCO® SERIES P90

115V and 230V Sealless Drum Pump Motors

For safe and fast transfer of corrosive liquids

- Lightweight, portable design
- Designed specifically for use with the Sethco Series P90 Drum Pumps
- On/off switch with built-in thermal overload
- Handles liquids with specific gravity up to 1.8 and maximum viscosity of 4,000 SSU
- Molded thermoplastic corrosion resistant housing



COMING SOON!
Variable Speed Control
& CE Certification

Specifications

Series	P90	
Model	381-U1	381-U2
Voltage	115V	230V
Phase	1	1
Hz	50/60	50/60
Power	525 w	560 w
Current	8 amps	4 amps
Insulation	Class B	Class B
Enclosure	Open Drip Proof	Open Drip Proof
Motor Weight	7.7 lbs (3.5 kg)	7.7 lbs (3.5 kg)
Cord Length	15 ft (4.6 m)	15 ft (4.6 m)



Notes:

- 1) Pump tubes available in Polypropylene (PP), Kynar (PVDF) or 316SS construction
- 2) Tube lengths available in 30" (762 mm), 40" (1016 mm), 50" (1270 mm), and 60" (1524 mm)
- 3) Capacities to 35 GPM (135 LPM)
- 4) Heads to 39 feet (12 m)
- 5) Maximum temperatures:
Polypropylene (PP): 130° F (55° C)
Kynar (PVDF) and 316SS: 240° F (116° C)



A Met-Pro Fluid Handling Technologies Business
Combining the Resources of Dean Pump, Fybroc & Sethco

www.mp-gps.com

